

★ HYDR = Q69 92-414318/50 ★ SU 1710929-A1
 Pipeline system damaged section automated detection - arranging
 sensors at test sections of highest leakage sensitivity and finding
 section with max. damage probability

HYDRO MECH SANITARY CONS WORK INST 89.02.22

89SU-4682691


T01 X25 (92.02.07) F17D 5/02

The pipeline damage section automatic detection, including setting pressure sensors at test sections, followed by setting their polling sequence and their polling timing, while determining of damaged section is indicated by the pressure variation magnitude, for better reliability, involves setting of sensors at sections with highest leakage sensitivity. For that prior to the operation of leakage searching, the hydraulic network analysis is carried out by computer, for comparing the sensitivity of the units by formation of sensitivity matrix using a given formula.

The hardware includes pressure sensors (1), computer (2), pressure-to-electric signal converter (3), data transmission unit (4), communication channel (5), data receiver (6), matching unit (7), printer (8) and data display system (9).

USE/ADVANTAGE - For detecting-localising damages of pipelines for all urban pipelines network. Better reliability, efficiency and accuracy of detecting damage and its localisation. Bul.5/7.2.92. (4pp Dwg.No.1/1)

N92-315885



© 1992 DERWENT PUBLICATIONS LTD.

128, Theobalds Road, London WC1X 8RP, England

US Office: Derwent Inc., 1313 Dolley Madison Boulevard,

Suite 401 McLean, VA22101, USA

Unauthorised copying of this abstract not permitted.